Grigolin evoluzioni costruttive

GrigoKoll® Adesivi per piastrelle

GUIDELINE FOR FLOORS AND WALLS ADHESIVE SELECTION

numbers in blocks indicate in cm the maximum lenght of the tile's longer side

								FAST ADHESIVES FOR MARBLES AND NATURAL STONES			EPOXY-POLYURETHANE ADHESIVE
		GRIGOKOLL PLUX	GRIGOKOLL PROX	GRIGOKOLL FLEX	GRIGOKOLL TEX	GRIGOKOLL MAX	GRIGOKOLL ULTRAX	GRIGOKOLL RAPIDUX	GRIGOKOLL VELOX	GRIGOKOLL GENIUX	GRIGOKOLL OMNIX
	Classification EN 12004	C1	C1TE	C2TE	C2TE	C2TES1	C2TES1	C2FT	C2FTS1	C2TE S2	R2T S2
EXTERIOR	SUITABLE SURFACES										
	cured concrete			60	90	120	120	90	90	120	120
	cement screeds			60	90	120	120	90	120	120	120
	flexible water-proofings			60	90	120	120	90	120	120	120
	cement plasters			30	30	90	90	60	90	120	120
INTERIOR	cured concrete			90	90	120	120	90	120	360	360
	cement screeds	30	60	120	120	360	360	120	360	360	360
	heating/cooling screeds	30	30	90	90	180	180	90	180	360	360
	fluid cement screed, normal and heating/ cooling	30	30	90	90	180	180	90	180	360	360
	fluid anhydrite screed, normal and heating/ cooling			90	90	180	180	90	180	360	360
	old ceramic floors			60	60	120	120	90	120	360	360
	wood conglo-merate panels										90
	cement base blocks or panels	30	30	90	90	120	120	90	120	360	120
	plaster boards			60	60	90	90	90	90	120	120
	gypsum panels			60	60	90	90	90	90	120	120
	flexible water-proofings	30	30	90	90	120	120	90	120	360	360
	Steel/PVC										90
SWIMMING POOL	cured concrete			30	30	120	120	90	90	120	120
	cement screeds			60	60	120	120	60	90	120	120
	flexible water-proofings			60	60	90	90	60	90	120	120
	Steel/PVC										90

use not allowed

surface abrasion advised

speciific primer treatment necessary

fast curing

epoxy-polyurtehane bi-component adhesive